



**Product Name :**  
Foot Impulse Sealing Machine

**Product Code :**  
EQUP-MC20086-0005

**Description :**

Foot Impulse Sealing Machine

**Technical Specification :**

Capacity Variable  
Automatic Grade Semi-Automatic  
Condition New  
Voltage 220  
Type Sealing  
Weight 35 kg  
Power Supply singhal Phase  
Max. Sealing 125 mm  
Power 220  
Adjustable Seal Head Yes  
Is It Resistant to Corrosion Resitant  
Application Sealing Machine

Using the best grade components, we are successfully manufacturing, trading, distributing, retailing, importing and supplying Foot Impulse Sealing Machine. Provide perfect sealing of tea, confectionery, wafers, snacks, powder pouches, this impulse sealing machine is specifically designed using high grade material and leading techniques. To meet the various needs of our customers, the offered impulse sealing machine is availed in different specifications.

**Features:**

- Ergonomic design
- Lightweight
- Better efficiency

**Other Details:**

- Foot sealer sealing machine suitable for 1/2 kg to 25 kg pouch high Quality of Sealing
- Accurate sealing of pouch packing machine like tea
- Confectionery, wafers, snacks, powder
- Very fast production and low maintenance
- LD, PP, BOPP all the pouch you can seal it

| Sealing Length | Sealing Width | Watts  | Voltage Supply |
|----------------|---------------|--------|----------------|
| 8              | 3 mm to 5 mm  | 500 w  | 220 v          |
| 12             | 3 mm to 5 mm  | 700 w  | 220 v          |
| 16             | 3 mm to 5 mm  | 900 w  | 220 v          |
| 20             | 3 mm to 5 mm  | 1200 w | 220 v          |
| 24             | 3 mm to 5 mm  | 1400 w | 220 v          |
| 28             | 3 mm to 5 mm  | 1600 w | 220 v          |
| 32             | 3 mm to 5 mm  | 1800 W | 220 V          |
| 36             | 3 mm to 5 mm  | 2000 W | 220 V          |
| 40             | 3 mm to 5 mm  | 2200 W | 220 V          |



**Equip Machines China**

**Email us at: [sales@equipmentsmachines.com](mailto:sales@equipmentsmachines.com)**